

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other

2. NAME OF OPERATOR

PREMIER PRODUCTION COMPANY

3. ADDRESS OF OPERATOR

324 W. Main Artesia, New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FEL 660' FSL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

☐  
☐  
☒  
☐  
☐  
☐  
☐  
☐

(other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

-22-82; Rig/up & perforated 2942', 43, 44, 46, 47, 51, 52, 53, & 56; 10 Shots .50" holes (San Andres) Set Packer & Treated W/1000 Gal. 20% NEFE Acid./ Flush W/5 BBL 2% KCL Water. Swabbed 24 Hrs. 100% Oil 74 BBL Water. 1-26-82 Set Cast Iron Bridge Plug At 2900' to shut off San Andres. Zone

-26-82; Perforated 1ST Stage; 2774, 75, 77, 78, 85, 86, 87, 89, 90, & 91; (Anderson Sand) 10 Shots .50" holes. 2ND Stage; 2534', 35, 36, 37, 38, 39, 40, 41, 42, & 43; (Loco Hills Sand) 10 Shots .50" holes. 3RD Stage; 2080', 81, 82, 83, 84, 85, 86, 87, 90, & 91; (Queen Sand) 10 Shots .50" holes. Set Packer & RBP & Treated Perfs. 2774'-91'. W/750 Gal. 10% MCA Acid & Swabbed 24 Hrs. Trace-Oil/24 bbls water; 1-28-82; Set Packer & RBP & Treated Perfs. 2534'-43'. W/500 Gal 10% MCA Acid/Swabbed 24 Hrs. Trace of oil /Acid Water. Set Packer & RBP & Treated Perfs. 2080'-91' W/ 500 Gal. 10% MCA Acid/ Swabbed 2 1/2 Hrs. No OIL/ Acid Water Only Shut Down To FRac.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE [Signature] DATE 2-16-82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

5. LEASE

Fed. LC 055696

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

FEB 17 1982

8. FARM OR LEASE NAME

O. C. D.

YATE PREMIER FEDERAL ARTESIA, OFFICE

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

UNDES. SAN ANDRES

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

SEC. 22 T 18 S R 29 E.

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

GL 3466

(NOTE: Report results of multiple completion or zone change on Form 9-330)