

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR  
PREMIER PRODUCTION COMPANY

3. ADDRESS OF OPERATOR  
324 W. Main Artesia New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FEL 660' FSL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE RECEIVED  
FED. LC 055696  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
FEB 17 1982  
7. UNIT AGREEMENT NAME  
O. C. D.  
8. FARM OR LEASE NAME ARTESIA OFFICE  
YATES PREMIER FEDERAL  
9. WELL NO.  
10. FIELD OR WILDCAT NAME  
UNDES. SAN ANDRES  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SEC 22 T 18 S R 29 E  
12. COUNTY OR PARISH 13. STATE  
Eddy New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
GL 3466

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1-29-82; SET PACKER & RBP & FRAC'D Thru Perfs. 2774'-91'. 10 Perfs W/ 20000 Gal. Gel & 2% KCL Water & 16,000 # 20-40 Sand & 5500 # 10-20 Sand. SHUT IN 2 HRS. & Flo'D Back 40 BBLS Water.

SET PACKER & RBP TO FRAC THRU PERFS. 2534'-43'. 10Perfs. W/20,000 Gal Gel/2% KCL Water & 16,000 # 20-40 sand & 5500 # 10-20 Sand. Shut in 6 Hrs. & Flo'd Back 50 BBLS overnit

1-30-82; SET PACKER & RBP & FRAC'D Thru Perfs. 2080'-91'. 10 Perfs. W/21,000 GAL Gel/2% Kcl Water & 18,500 # 20-40 Sand & 7000# 10-20 Sand. Shut in 24HRS. Flo'd back 20Cal. Min.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Premier Production*

TITLE

*Henry J. ...*

DATE

2-17-82

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: