

UNITED STATES
DEPARTMENT OF THE INTERIOR
C/SF GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐
well well other

2. NAME OF OPERATOR

PREMIER PRODUCTION COMPANY 748-2093 /

3. ADDRESS OF OPERATOR

324 W. Main Artesia, New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FEL 660' FSL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐
☐
☐

RECEIVED
FEB 23 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1-22-82; Rig/up & perforated 2942', 43, 44, 46, 47, 51, 52, 53, & 56; 10 Shots .50" holes (San Andres) Set Packer & Treated W/1000 Gal. 20% NEFE Acid./ Flush W/5 BBL 2% KCL Water. Swabbed 24 Hrs. 2% Oil 74 BBL Water. 1-26-82 Set Cast Iron Bridge Plug At 2900' to shut off San Andres. Zone

1-26-82: Perforated 1ST Stage; 2774, 75, 77, 78, 85, 86, 87, 89, 90, & 91; (Anderson Sand) 10 Shots .50" holes. 2ND Stage; 2534', 35, 36, 37, 38, 39, 40, 41, 42, & 43; (Loco Hills Sand) 10 Shots .50" holes 3RD Stage; 2080', 81, 82, 83, 84, 85, 86, 87, 89, & 91; (Queen Sand) 10 Shots .50" holes. Set Packer & RBP & Treated Perfs. 2774'-91'. W/750 Gal. 10% MCA Acid & Swabbed 24Hrs. Trace-Oil/24bbbls water; 1-28-82; Set Packer & RBP & Treated Perfs. 2534'-43'. W/500 Gal 10% MCA Acid/Swabbed 2Hrs. Trace of oil /Acid Water. Set Packer & RBP & Treated Perfs. 2080'-91' W/ 500 Gal. 10% MCA Acid/ Swabbed 2 1/2 Hrs. No OIL/ Acid Water Only Shut Down To FRac.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert A. Chapman
ROBERT A. CHAPMAN

TITLE Geologist

DATE 2-17-82

(This space for Federal or State office use)

APPROVED BY FEB 26 1982
CONDITIONS OF APPROVAL OF _____

TITLE _____ DATE _____

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

* You will HAVE TO SET 35' OF CEMENT
WITH BAILER ON CAST IRON BRIDGE PLUG
AT 2900'

*See Instructions on Reverse Side

RECEIVED

MAR 12 1982

O. C. D.
ARTESIA, OFFICE