

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Petr Corp</u>		Lease <u>Copeland "SM" Com</u>		Well # <u>1</u>	
Location of Well	Unit <u>1980N 2310W F</u>	Section <u>25</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor <u>Landis Rig #4</u>			Type of Equipment <u>Rotary ASAP</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot Cnd.	New or Used	Depth	Sacks Cement
<u>24"</u>	<u>20</u>			<u>80'</u>	<u>Red. Mix</u>
<u>17 1/2</u>	<u>13 3/8</u>	<u>48# J-55</u>		<u>400'</u>	<u>375 SX Circ</u>
<u>12 1/4</u>	<u>8 5/8</u>	<u>24# J-55</u>		<u>1200'</u>	<u>600 SX Circ</u>
<u>7 7/8</u>	<u>5 1/2 - 4 1/2</u>	<u>105# - 17#</u> <u>10.5 - 11.6#</u>		<u>9565</u>	<u>375 SX</u>

Casing Data:

Surface 31 joints of 8 3/4 inch 24 # Grade J-55

yes

(Approved) (Rejected)

Inspected by B.W. Weaver date 5-13-82

Cementing Program

Size of hole 12 1/4 Size of Casing 8 3/4 Sacks cement required 150

Type of Shoe used Guide Float collar used Insert Btm 3 jts welded yes

TD of hole 1205 Set 1207 Feet of 8 3/4 inch 24 # Grade J-55

New-used csg. @ 1207 with 150 sacks neat cement around shoe

+ 450 sax Hewco lite additives

Plug down @ 5:00 (~~AM~~) (PM) Date 5-13-82

Cement circulated No No. of Sacks

Cemented by Hewco Witnessed by B.W.

Temp. Survey ran @ 1130 (~~AM~~) (PM) Date 3-13-82 top cement @ 800

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last Drilling Break @ 1048

Ran 1" to 712 Ft and circulated cement to surface