

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
NM OIL CONS. COMM. DIV.
Artesia, NM 88210

Form approved.
Budget Bureau No. 42-R1424.

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation. Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

5. LEASE DESIGNATION AND SERIAL NO.

LC046256C

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Holly Federal

9. WELL NO.

1.

10. FIELD AND POOL, OR WILDCAT

Undesignated (Morrow)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 5, T-18-S, R-30-E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

1100 Wall Towers West, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' FEL & 760' FSL, Sec. 5, T-18-S, R-30-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3553.1' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set 8 5/8" Intermediate csg

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drill 11" hole to 3350'. CCM to run logs. Ran CNL/FDC/GR-Caliper, BVI & DLL logs. CCM to run csg. Ran 77 jts 8 5/8" 24# & 28# K-55 & S-80 ST&C csg (3388'). Set @ 3350'. Cmt w/1800 sx Lite wt cmt, 12# salt, 5# Gilsonite, 1/4# Flocele/sx & 400 sx Class "C" cmt 2% cc. PD @ 10:30 P.M. 4-6-82. Circ 100 sx. Set slips on 8 5/8" csg.

Top 1223' 8 5/8" 28# S-80 ST&C

Bottom 2127' 8 5/8" 24# K-55 ST&C

Total 3350'

ACCEPTED FOR RECORD

APR 20 1982

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

RECEIVED
APR 20 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct.

SIGNED

District Operations Engineer, 4/16/82

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: