

Artesia, NM 88210

sf/file

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR Premier Production Company
3. ADDRESS OF OPERATOR 324 W Main, Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650 FSL 990 FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Spud well ☐

5. LEASE
Fed LC 055696
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Yates Premier Federal
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Undesignated San Andres
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 22, 18S 29E
12. COUNTY OR PARISH Eddy 13. STATE NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3479'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 5/31/82; drilled 12 1/4" hole to 355'; set 330' of new 8-5/8" 24# K-55 API casing w/shoe & 1 centralizer. Cemented w/300 sax Class C 2% CalCl; cement did not circulate. Wait 6hr, run temp survey; top of cement at 200' below surf. Tagged 1" line at 170' below surf & cemented w/200 sax Class C 2% CalCl, 200gal flo-chek; cement to surf; shut down, WOC. 6/2 Drilled cement plug, tested to 1000#, held OK. Continued drilling 7-7/8" hole w/10# brine to 3300'. TD 6/10/82. Set 3300' 4 1/2" 10.5# K-55 new API casing w/shoe & 10 centralizers. Cemented w/1000 sax Haliburton lite & 400 sax Class C 2% CalCl; circulated to surface, 150 sax to pit. Tried to bump plug, it wouldn't go; press to 3500#; calculated 3200' cement in hole. 6/12 - 6/14 Drilled out cement to base of shoe.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Operator DATE 6-16-82

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: _____

JUL 1 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

RECEIVED
JUN 21 1982
OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO