

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP. DATE*
(Other Instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 067132

6. IF INDIAN, ALLOTTEE RECEIVED

MAY - 6 1982

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME C. D.

Denton Federal Office

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

San Andres Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

S-22 T-18S R-29E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Ray Westall /

3. ADDRESS OF OPERATOR

P.O. Box 4 Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

1880' FSL & 2080' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3448 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

Spud, 8 5/8, 4 1/2 and T.D.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-18-82 Spud with 12 1/4" bit. Ran 368' of 8 5/8" 23# casing. Cemented at 380' with 400 sx. Class "C" 4% CaCl cement. Circulated to surface, changed bit to 7 7/8".

4-19-82 WOC 18 hours pressured up to 1,000# for 30 minutes held O.K.

4-25-82 T.D. 3140', Ran 3138' of 4 1/2" 10 1/2# J55 casing. Set and cemented with 475 sx 50/50 poz mix 6/10% of CF9 3/10% of TF4 3/10% KCL and 320 sx Class "C" 4% CaCl. Circulated to surface. Float held WOC 24 hours.

RECEIVED
APR 29 1982

ACCEPTED FOR RECORD
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

MAY 5 1982

DATE 4-27-82

18. I hereby certify that the foregoing is true and correct

SIGNED

Ray Westall

TITLE

Operator

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO