

DISTRIBUTION		
SANTA FE	1	
FILE	1	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	1	

P. O. BOX 2088
SANTA FE, NEW MEXICO 875

FORM C-10
REVISED 1

5a. Indicate Type of Lease
State ☐ Free

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

RECEIVED

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Ralph Nix

Address of Operator

P. O. Box 617 Artesia, New Mexico 88201

Location of Well

UNIT LETTER K 1650 FEET FROM THE South LINE AND 2310 FEET FROM
THE West LINE, SECTION 27 TOWNSHIP 18S RANGE 26E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Kelly

9. Well No.

2

10. Field and Pool, or Wildcat

Und Atoka Yeso

11. Elevation (Show whether DF, RT, CR, etc.)

3345' GL

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

REPAIR OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☐

OTHER Perforation & Stimulation

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/26/82 Dresser Atlas set cast iron bridge plug @ 3570' w/4x cement plug on top & perforated 13 holes w/3 1/4" E gun @ 3086, 3114, 34, 41, 3225, 31, 43, 55, 3305, 17, 28, 45, 62.

8/30 & 8/31/82

Perforate 12 additional holes in lower yeso as follows: 3095, 3110, 3220, 36, 49, 66, 80, 90, 99, 3332, 48, 68. Upper Yeso perms, first run @ 2571', 86, 2608, 21, 44, 66, 97, 2706, 29, 48, 2824, 43, 61, 95, 2956, 71. Second run @ 2614, 38, 75, 84, 2720, 53, 77, 85, 2800, 38, 58, 78, 85, 2900, 08, 17.

Lower Yeso gel H₂O Frac; 80,000 gal gelled 1% KCL water carrying 160,000# 20/40 sand & 20,000# 10/20 sand, average rate 80 bbls per minute, average PSI 3000, maximum PSI 3900. Upper Yeso fractured w/100,000 gals gelled 1% KCL water carrying 200,000# of 20/40 sand & 30,000# 10/20 sand average rate 80 bbls per minute, average PSI 3000.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

TITLE

DATE

9/8/82

TITLE

SUPERVISOR, DISTRICT II

DATE

SEP 13 1982