

NM OIL CONS. COM. STION
Drawer DD UNITED STATES
Artesia, NM 88210 DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-01159

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Holly Federal #4

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Undesignated (Atoka)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 4, T-18-S, R-30-E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

1. OIL ☐ GAS ☒ OTHER ☐

DEC 3 1982

2. NAME OF OPERATOR

Southland Royalty Company ✓

O. C. D.

3. ADDRESS OF OPERATOR

21 Desta Drive, Midland, Texas 79701

ARTESIA, OFFICE

RECEIVED

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface 9 1980 W

1980 FWL & 660' FSL, Sec. 4, T-18-S, R-30-E DEC 14 1982

O. C. D.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, ARTESIA, OFFICE

3539.7' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Set 8 5/8" Intermediate Csg xx

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drill 12 1/4" hole to 3350'. CCM to run csg. Ran 75 jts 8 5/8" 24# & 28# K-55 & S-80 ST&C csg (3358'). Set @ 3350'. Cmt w/1350 sxs lite wt cmt, 12# salt, 1/4# Flocele & 5# Gilsonite/sx & 200 sx Cl "C" cmt 2% CaCl. PD @ 5:30 AM 11-23-82. Circ 75 sxs.

Top 1168' 8 5/8", 28#, S-80, ST&C

Bottom 2190' 8 5/8", 24#, K-55, ST&C

Total 3358'

18. I hereby certify that the foregoing is true and correct

SIGNED F.N. RAD by D. Robato

District Operations Engineer

DATE 12-3-82

(This space for Federal use)

ACCEPTED FOR RECORD

APPROVED BY (ORIG. SGD.) DAVID R. GLASS

CONDITIONS OF APPROVAL DEC 13 1982

DATE