

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Yates Pet. Co.		Lease Tumbleweed QM		Well # 1	
Location of Well	Unit D	Section 15	Township 18	Range 25	County Cddy
Drilling Contractor	ARD		Type of Equipment Rotary		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17.5	13.375	48#	New	Appx. 360'	circ.
12.25	8.625	24#	"	1200'	circ.
7.5	4 1/2 or 5 1/2	9.5 or 15.5	"	TD	400 sx.

Casing Data:

Surface 30 joints of inch 24 # Grade K-55

(Approved) (Rejected)

Inspected by M.S. date 9/29/82

Cementing Program

Size of hole 12 1/4" Size of Casing 8 5/8" Sacks cement required

Type of Shoe used guide Float collar used Insert Btm 3 jts welded yes

TD of hole 1210' Set 1210' Feet of 8 5/8" Inch 24 # Grade K-55

(New) used csg. @ 1210' with 2002% sacks need cement around shoe
+ 410 sax Pacemaker C additives (1/4# celoseal, 2% cc)

Plug down @ 6:30 (AM) (PM) Date 9/29/82

Cement circulated Yes No. of Sacks 10 sx

Cemented by Western Co. Witnessed by Mike Stillfield

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks:

No centralizers
Lost circ. @ 1020' repaired
Lost dily break @ 1044'