

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Ralph Nix</u>		Lease <u>Merrill</u>		Well # <u>2</u>	
Location of Well	Unit <u>B</u>	Section <u>34</u>	Township <u>18S</u>	Range <u>26E</u>	County
Drilling Contractor	<u>Salazar Bros.</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
9 1/2"	8 5/8"	24 #	<u>New</u>	910	525 circ
6 1/4"	5 1/2"	15.5 #	"	TD	375 circ

Casing Data:

Surface 22 joints of 8 5/8 inch 24 # Grade J-55
Yes (Approved) (Rejected)

Inspected by BW Weaver date 9-9-82

Cementing Program

Size of hole 9 1/2 Size of Casing 8 5/8 Sacks cement required 200

Type of Shoe used Guide Float collar used Insert Btm 3 jts welded yes

TD of hole 925 Set 920 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 920 with 200 sacks neat cement around shoe
+ 300 sack Hawco lite additives

Plug down @ 6:15 (AM) (PM) Date 9-9-82

Cement circulated yes No. of Sacks 35

Cemented by Hawco Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Loss Circulation @ 600 Last Drilling Break @ 790