Drawer		JCT -
Lec. 1973 UNITED FAICE VF DEPARTMENT GEOLOGIUS SURVEY	La., NM 210 Form Approved. Budget Bureau No. 42-R1424 5. LEASE LC 055696 6. IF INDIAN, ALLOTTEE OR TRIBE NAME	6  <b>2</b> '
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to de OHn & GAS back to a different reservoir. Use Form 9-331-C for such proposals to de OHn & GAS back to a different minerals NGMT. SERVICE 1. oil gas roother 2. NAME OF OPERATOR Martin Yates III (MYCO) 3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1650 FSL 1650 FWL, Sec. 14-18S-29E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	<ul> <li>7. UNIT AGREEMEN RECEIVED</li> <li>8. FARM OR LEASEWAME Boulter Federal NOVID 1992</li> <li>9. WELL NO. 4</li> <li>9. WELL NO. 4</li> <li>10. FIELD OR WILDOAT NAMERTESIA, ON GE Loco Hills-QN-GB-SA</li> <li>11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit K, Sec. 14-T18S-R29E</li> <li>12. COUNTY OR PARISH Eddy</li> <li>13. STATE NM</li> </ul>	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA         REQUEST FOR APPROVAL TO:       SUBSEQUENT REPORT OF:         TEST WATER SHUT-OFF	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3478' GR (NOTE: Report results of multiple completion or zone change on Form 9-330.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

WIH and perforated 3661-3836' w/15 .50" holes as follows: 3661, 68, 78, 87, 3722, 39, 65, 71, 80, 89, 96, 3812, 20, 30, 36'. RIH w/tubing and packer. Spotted acid across perforations. Set packer and treated w/1500 gallons 20% NEA and 10 balls. Flowed well back with no show of oil or gas. POOH. Set CIBP at 3600'. WIH and perforated 3395-3400' w/10 .50" holes (2 SPF). RIH with tubing and packer. Set packer at 3386' and swabbed dry. Ran swab, tubing dry. Treated with 1000 gallons 15% NEA. Swabbed back load and sulfur water. No show of oil or gas.

Subsurface Safety Valve: Manu. and Type		Ft.
18. I hereby certify that the toregoing is true and correct		L Contraction of the second se
SIGNED L'anter or ellet TITLE Engineering Se	ecty date <u>10-27-82</u>	
ACCEPTED FOR RECORDis space for Federal or State offic APPROVED BY	ce use) DATE	
CONDITIONS OF APPROVINCE ANY 8 1982		
U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO • See Instructions on Reverse Si	ide	Ň

and the liter contraction of the second