

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPI  
(Other instructions  
verse side)

Budget Bureau No. 1004-0.1.1.  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

LC-028978B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.)

At surface

660' FNL & 1980' FEL

14. PERMIT NO.

API #30-015-25121

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3419' GR

MAY 11 '88

O. C. D.

ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Benson Deep Fed. ET Com

9. WELL NO.

1

10. FIELD AND POOL OR WILDCAT

Benson-Strawn

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Unit B, Sec. 33-T18S-R30E

12. COUNTY OR PARISH 13. STATE

Eddy

nm

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other) Abandon Morrow, test Strawn

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TIH with packer and standing valve to 11571'. Set packer. Swabbed well. Perforated 10801-808' w/14 .42" holes (2 SPF). Acidized perforations 10801-808' w/1500 gals 15% NEFE acid and ball sealers. Swabbed well. Released packer. Set RBP at 10700', tested OK. Spotted 20' sand on plug. Perforated 4 squeeze holes at 8650'. Squeezed perfs to 1500 psi w/125 sx Class "H" cement +.5% Halad-22 + .3% CFR-3. WIH and perforated 8230' w/2 holes. Set cement retainer at 8150' and squeezed perfs w/75 sx cement to 1600 psi.

Work began 4-26-88 through 4-29-88.

Past 70-2  
5-20-88  
P + A Mor.

18. I hereby certify that the foregoing is true and correct

SIGNED *Granite S. S. S.*

TITLE Production Supervisor

DATE 5-3-88

(This space for Federal or State office use)

APPROVED BY

TITLE

ACCEPTED FOR RECORD

CONDITIONS OF APPROVAL, IF ANY:

MAY 9 1988

\*See Instructions on Reverse Side

SJS  
CARLSBAD, NEW MEXICO

