

RECEIVED

MAR 1 8 54 AM '93
CARL AREA

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different well.
Use "APPLICATION FOR PERMIT—" for such proposals.

NM OIL & GAS COMMISSION
Drawer DD
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NMNM17223

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Alice Federal #1

9. API Well No.

30015243740051

10. Field and Pool, or Exploratory Area

Turkey Track (SR,Q,GB,SA)

11. County or Parish, State

Eddy County, NM

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Premier Production Company

3. Address and Telephone No.

P.O. Box 1246, Artesia, NM 88210; (505) 748-2093

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Section 23: SW/4 SW/4
T-18S R-29E

wt.m

990' FSL & 330' FWL

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☒ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Plug & Abandon
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged & abandoned well as per requirements. Ran 2" tubing to 2417'; circulated hole with 10# gelled mud. Spotted 50 sx cement plug from 2417' back to 1775'; trip out with tubing. W.O.C. 2½ hours; trip in with tubing. Tagged top of plug at 1793'; spotted bottom of tubing at 973'; spotted 25 sx cement plug. Spotted bottom of tubing at 400'; spotted 35 sx plug which circulated cement to surface. Installed and cemented 4" identifying marker at top of hole. Cleaned, ripped and levelled location; sloped for drainage. Ready for inspection.

Part ID-2
3-19-93
PJA

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Paul White

Title Consulting Engineer

Date 2/25/93

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

Title PETROLEUM ENGINEER

Approved by
Conditions of approval, if any:

Date 3-9-93