

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Ralph N. Cox</u>		Lease <u>Fox</u>		Well # <u>1</u>	
Location of Well	Unit <u>F</u>	Section <u>35</u>	Township <u>13</u>	Range <u>26</u>	County <u>EDDY</u>
Drilling Contractor	<u>Salazar</u>		Type of Equipment <u>Rotary</u>		
* <u>Witness</u> <u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <u>12 1/4"</u>	<u>3 5/8"</u>	<u>24 lb</u>	<u>New</u>	<u>910'</u>	<u>Circ</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>15.5 lb</u>	<u>"</u>	<u>3900'</u>	<u>Circ</u>
Casing Data: <u>3-4-83</u>					
Surface <u>23</u> joints of <u>8 5/8</u> inch <u>24</u> # Grade <u>J-55</u>					
<u>yes</u> (Approved) (Rejected)					
Inspected by <u>BLU Weaver</u> date _____					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 5/8</u> Sacks cement required _____					
Type of Shoe used <u>Tex-At</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>976</u> Set <u>978</u> Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>J-55</u>					
New-used csg. @ <u>978</u> with <u>200</u> sacks neat cement around shoe					
+ <u>300</u> sax <u>Hance lite</u> additives _____					
Plug down @ <u>7:00</u> (AM) (PM) Date <u>3-4-83</u>					
Cement circulated <u>yes</u> No. of Sacks <u>50</u>					
Cemented by <u>Hance</u> Witnessed by <u>BLU Weaver</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>Last Drilg Break 880</u>					