

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
RECEIVED

SUNDRY NOTICES AND REPORTS ON ANEBS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐

2. NAME OF OPERATOR
Anadarko Production Company

3. ADDRESS OF OPERATOR
P. O. Drawer 130, Artesia, New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 330' FEL Sec18, T18S, R29E
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

RECEIVED
SUBSEQUENT REPORT OF:

JUL 05 1983

O. C. D.
ARTESIA, OFFICE

X - Spud, drill TD, set surface & production csg.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Rigged up rotary tools; spudded 12 1/4" hole @ 9:15 PM 6-12-83; lost circulation @ 63'; drilled to 362' KB with fresh water.
2. Ran 8-5/8", 24# casing with casing shoe @ 360' KB. Halliburton cemented with 350 sx Class H with 2% CaCl₂; PD @ 11:00 AM 6-13-83; cement did not circulate. Pete Hines approved readymixing to surface with 13 yards of 1/4" with 3% CaCl₂.
3. Installed BOP and pressure tested to 1000#. WOC 19 hours prior to drilling plug on 8-5/8" with 7-7/8" bit. Drilled to TD 2802' with 10# Brine water; ran O. H. Logs.
4. Ran 5 1/2", 15.5#, ST&C casing with casing shoe @ 2801' KB. Halliburton cemented with 700 sx HL w/8# Salt/sx & 1/4# Flocele/sx and tailed-in with 250 sx Class H w/5# Salt/sx, .5 of 1% CFR-2 and 10# No. 3 sand/sx. PD @ 1:30 AM 6-20-83; circulated 50 sx to pit.

Note: Jim Ward with USGS witnessed cementing job.

Note: Will file appropriate forms upon completion of well.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Area Supervisor DATE June 21, 1983

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 30 1983

*See Instructions on Reverse Side

ROSWELL, NEW MEXICO