

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator Ralph Nix		Lease Merrill Bttry #		Well # 4	
Location of Well	Unit H	Section 34	Township 18	Range 26	County Eddy
Drilling Contractor	Salazar		Type of Equipment Rotary		

\* APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* 12 1/4	8 5/8	24#	New	950	Circ
7 1/8	5 1/2	15.5#	"	4000	Circ

Casing Data:

Surface 23 joints of 8 5/8 inch 24 # Grade J-55

Yes (Approved) (Rejected)

Inspected by B.W. Weaver date 3-20-83

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required

Type of Shoe used Tex-Bt Float collar used Insert Btm 3 jts welded Yes

TD of hole 973 Set 975 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 975 with 200 sacks neat cement around shoe

+ 300 sax Howco lite additives 1/4 Flo Seal 6% Tel 2% CC

Plug down @ 9.30 (AM) (PM) Date 3-21-83

Cement circulated NO No. of Sacks

Cemented by Howco Witnessed by B.W. Weaver

Temp. Survey ran @ 330 (AM) (PM) Date 3-21-83 top cement @ 822

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Loss zone 822 Last Drilling Break 848

Run 1" to 620 ft Run 35 SX C 4% CC

574 " 35 SX C 4% CC

574 " 35 SX C 4% CC

572 " 35 SX C 4% CC

464 " 35 SX C 4% CC

332 " 35 SX C 4% CC

134 " 25 SX C 4% CC

To surface " 100 SX C