

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

APR 29 1983

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	OG-647	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT ARTESIAN WELL. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

O. C. D.
ARTESIAN OFFICE

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Delmer W. Berry	8. Farm or Lease Name Toomey Allen
3. Address of Operator 2401 Loma Drive Artesia, New Mexico 88210	9. Well No. #17
4. Location of Well: UNIT LETTER <u>0</u> <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>28</u> TOWNSHIP <u>18S</u> RANGE <u>28E</u> NMPM.	10. Field and Pool, or Willcat Artesia Queen GR SA
15. Elevation (Show whether DF, RT, GR, etc.) 3550.9' GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <u>Perf & Acid job</u>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-9-83 Drilled to a total depth of 2850', was reached at 8:30 am.
Ran 2850' of 5½: 15.5# long string casing.
Used 4, 5½" centralizers.
Cemented with 250 sxs Halliburton Lite w/¼# flocele & 6# salt, & 300 sxs Class "C" neat w/ 3# salt.
Circulated 25 sxs.
WOC 18 hours.
Plug down at 5:50 p.m.
Pressure tested 1000# for 30 minutes: held fine.

4-21-83 Perforated at 2050', 52, 54, 56, 58, 62, 64, 66, 68, 70, 2072'.
Total shots: 11
Acidized with 15,000 gals 15% reg acid.
Fraced w/20,000 gals gelled 1% KCL water, w/30,000# 20/40 sand, & 10,000# 10/20 sand.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Victoria Juel TITLE Agent DATE April 29, 1983

APPROVED BY Lois A. Clements TITLE Supervisor DATE MAY 2 1983

CONDITIONS OF APPROVAL, IF ANY: