Form 9-331 Dec. 1973 UNITED STATES Artesia, NN 882 DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	Form Approved. Budget Bureau No. 42–R1424
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME RECEIVED 8. FARM OR LEASE NAME Bear Draw JUL 0 5 1983 9. WELL NO. 5 O. C. D.
 well well other 2. NAME OF OPERATOR Forister & Sweatt 3. ADDRESS OF OPERATOR PO Box 161, Artesia, NM 88210 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 2310 FEL 660 FSL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 	9. WELL NO. 5 O. C. D. 10. FIELD OR WILDCAT NAMERTESIA, OFFICE 4Bear Draw Q.GR.SA. 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 21 T16S R29E 12. COUNTY OR PARISH 13. STATE Eddy New Mexico 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3649.4 GR DEFENSION TO THE STATE OF THE STA

- Drilled 12¹/₄ hole, 350'. Ran 8 jts. 8 5/8 24# casing 338'. Set at 350'. Cemented with 50 sx Hal-Light thick set 5# gilsonite 1. 2# flocele 2% Cal Chor. 200 sx Class C with 2% Cal Chor. Plug down 10:00 p.m. 5/23/83. Cemented at 45' from surface-ready mixed 10 yards to surface.
- Drilled 7 7/8" hole to 2675". Ran 65 jts 2677.30 4½ 10.5 # j-55 casing. Set at 2675'. Cemented with 550 sx Hal-Light 6# salt ½# flocele. 250 sx Class C 50/50 poz mix 2% gel 6# salt 2. 3/10% CFR-2. Plug down 7:30 p.m. Cement top at 1150'.

Subsurface Safety Valve: Manu. and Typ	е			Ft.
18. I hereby certify that the foregoing is SIGNED	true and correct			
SIGNED Charling The	A C NITLE I	Partner	DATE 6/3/83	
	(This space for	Federal or State office	e use)	
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE		DATE	
			ACCEPTED FOR RECO	RÐ
			DP. TO	
	*See Instruc	ctions on Reverse Sid	de JUN 3 0 1983	