

C/87

RECEIVED
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
JUN 29 1983

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

ARTESIA, OFFICE

BUR. OF LAND MGMT
ROSSELL DISTRICT

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR

Anadarko Production Company

3. ADDRESS OF OPERATOR

P. O. Drawer 130, Artesia, New Mexico 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980.5' FSL & 1646' FWL

AT TOP PROD. INTERVAL: Same Sec. 6, T18S, R29E

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other)

X - Spud, drill TD, set surface & production csg.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Riggged up rotary tools; spudded 12 1/2" hole @ 9:00 AM 6-5-83; drilled to 358' KB with fresh water.
2. Ran 8-5/8", 24# casing with casing shoe @ 356' KB. Halliburton cemented with 350 sx Class H with 2% CaCl. PD @ 6:16 PM 6-5-83; circulated 50 sx to pit.
Note: Jim Ward witnessed cementing.
3. Installed BOP and pressure tested to 1000#. WOC 21 1/2 hours prior to drilling plug on 8-5/8" with 7-7/8" bit. Drilled to TD 2808' with 10# Brine water; ran O. H. Logs.
4. Ran 5 1/2", 15.5#, ST&C casing with casing shoe @ 2807' KB. Halliburton cemented with 700sx HL with 8# Salt/sx & 1/2# Flocele/sx and tailed-in with 250 sx Class H w.5 of 1% CFR-2, 5# Salt/sx & 10# No. 3 sand/sx. PD @ 11:45 AM 6-11-83; circulated 50 sx to pit.
Note: Pete Hines witnessed cementing job.
Note: Will file appropriate forms upon completion of well.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Area Supervisor

DATE

June 21, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

[Signature]

JUN 23 1983

*See Instructions on Reverse Side

ROSSELL, NEW MEXICO