

NEW MEXICO OIL CONSERVATION COMMISSION

AUG 10 1983

O. C. D.  
ARTESIA, OFFICE

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
647	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator David C. Collier ✓	8. Farm or Lease Name Welch <i>It.</i>
3. Address of Operator P.O. Box 798, Artesia, New Mexico 88210	9. Well No. #9
4. Location of Well UNIT LETTER <i>E J</i> , 2110 FEET FROM THE South LINE AND 1650 FEET FROM THE East LINE, SECTION 17 TOWNSHIP 18S RANGE 28E NMPM.	10. Field and Pool, or Wildcat Artesia Queen GR SA
15. Elevation (Show whether DF, RT, GR, etc.) 3620 <i>SL</i>	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/8/83 Drilled to a total depth of 2534' at 6:00 am.  
Ran 2532' of 5½, 15.5# new limited service.  
With 5½" guide shoe at 2532' & insert float at 2518'.  
6 joints of ruff coat at 2434-2481', 2298-2340', 2116-2252', 2028-2070'.  
Used 5, 5½" centralizers at 2518, 2390, 2252, 2116, 1982.  
Cemented w/375 sxs Halliburton Lite, 8# salt, ¼# flocele, & 200 sxs Class "C" neat, 3# slat, .3% CFR-2.  
Circulated 45 sxs.  
WOC 3 days.  
Plug down at 3:00 am.  
Pressure tested 1000# for 30 minutes - Float held fine.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>Leslie A. Clements</i>	TITLE Production Clerk	DATE 8/9/83
APPROVED BY _____	TITLE Original Signed By Leslie A. Clements Supervisor District 11	DATE AUG 11 1983
CONDITIONS OF APPROVAL, IF ANY:		