

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Pet. Co.</u>			Lease <u>DAYTON EY</u>		Well # <u>2</u>
Location of Well	Unit <u>P</u>	Section <u>21</u>	Township <u>18</u>	Range <u>26</u>	County <u>EDDY</u>
Drilling Contractor	<u>LARUE #2</u>		Type of Equipment <u>Rotary</u>		

\* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 1/2</u>	<u>10 3/4"</u>	<u>32 #</u>	<u>NEW</u>	<u>350'</u>	<u>CIRC.</u>
* <u>9 1/2</u>	<u>7"</u>	<u>30 #</u>	<u>NEW</u>	<u>1150'</u>	<u>CIRC.</u>
<u>6 1/4</u>	<u>4 1/2"</u>	<u>10.5 #</u>	<u>NEW</u>	<u>TD</u>	<u>150 SX</u>

Casing Data:

Surface \_\_\_\_\_ joints of \_\_\_\_\_ inch \_\_\_\_\_ # Grade \_\_\_\_\_  
(Approved) (Rejected) \_\_\_\_\_

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 9 7/8 Size of Casing 7" Sacks cement required \_\_\_\_\_

Type of Shoe used Tex-Pat Float collar used Insert Btm 3 jts welded Yes

TD of hole 958 Set 968 Feet of 7 Inch 23 # Grade J-55

New-~~used~~ csg. @ 968 with 125 sacks neat cement around shoe

+ 175 sax Pace Setter lite additives 3% CC

Plug down @ 4:15 (AM) (PM) Date 8-3-83

Cement circulated Yes No. of Sacks 20 SX

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_