

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

| | |
|------------------------|-------------------------------------|
| NO. OF COPIES RECEIVED | |
| DISTRIBUTION | |
| SANTA FE | <input checked="" type="checkbox"/> |
| FILE | <input checked="" type="checkbox"/> |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | <input checked="" type="checkbox"/> |

AUG 02 1983

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

O. C. D.
ARTESIA, OFFICE

| | |
|--|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | 5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/> |
| 2. Name of Operator Yates Petroleum Corporation | 5. State Oil & Gas Lease No. |
| 3. Address of Operator 207 South 4th St., Artesia, NM 88210 | 7. Unit Agreement Name |
| 4. Location of Well UNIT LETTER N 330 FEET FROM THE South LINE AND 2310 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 18S RANGE 26E NMPM. | 8. Farm or Lease Name Eads GA |
| | 9. Well No. 2 |
| | 10. Field and Pool, or Wildcat Atoka-San Andres |
| 15. Elevation (Show whether DF, RT, GR, etc.) 3319' GR | 12. County Eddy |

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOBS ☒
OTHER Production Casing ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 14-3/4" hole 8:30 AM 7-27-83. Ran 9 jts of 10-3/4" 40.5# J-55 ST&C casing set 340'. 1-Texas Pattern notched guide shoe set 340'. Insert float set 297'. Cemented w/225 sx Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 3:34 PM 7-27-83. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 10 sx. Cement fell back. Ready-Mixed to surface w/3-1/2 yards. WOC. Drilled out 3:45 AM 7-28-83. WOC 12 hrs. Cut off and welded on flow nipple. Reduced hole to 9-7/8". Drilled plug and resumed drilling. Lost returns 212'. Pumped pill and regained returns. Ran 31 jts of 7" 20# J-55 ST&C casing set 952'. 1-Texas Pattern notched guide shoe set 952'. Insert float set 922'. Cemented w/125 sx Pacesetter Lite and 3% CaCl2. Tailed in w/125 sx Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 1:30 AM 7-29-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 15 sx. WOC. Drilled out 7:30 PM 7-29-83. WOC 18 hrs. NU and tested to 1000 psi for 30 minutes, okay. Reduced hole to 6-1/4". Drilled plug and resumed drilling. TD 1800'. Ran 45 jts of 4-1/2" 9.5# J-55 ST&C casing set 1800'. 1-float guide shoe set 1800'. Cemented w/200 sx Class "C" and .4% CFR-9. Compressive strength of cement - 800 psi in 12 hrs. PD 2:15 AM 8-1-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 15 sx. WOC 18 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements

TITLE Production Supervisor

DATE 8-2-83

Original Signed By
Leslie A. Clements
Supervisor District II

APPROVED BY _____

TITLE _____

DATE AUG 03 1983

CONDITIONS OF APPROVAL, IF ANY: