

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Ref. Co.</u>			Lease <u>EADS GA</u>		Well # <u>2</u>
Location of Well	Unit <u>N</u>	Section <u>22</u>	Township <u>18</u>	Range <u>26</u>	County <u>EDDY</u>
Drilling Contractor	<u>LABUE # 2</u>		Type of Equipment <u>ROTARY</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 1/2</u>	<u>10 3/4 "</u>	<u>32 #</u>	<u>NEW</u>	<u>350'</u>	<u>circ.</u>
* <u>9 1/2</u>	<u>7 "</u>	<u>30 #</u>	<u>"</u>	<u>1150'</u>	<u>circ.</u>
<u>6 1/4</u>	<u>4 1/2 "</u>	<u>10.5 #</u>	<u>"</u>	<u>TD</u>	<u>150 SX</u>

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 9 7/8 Size of Casing 7 Sacks cement required _____

Type of Shoe used Tex-Pat Float collar used Insert Btm 3 jts welded yes

TD of hole 950 Set 956 Feet of 7 Inch 32 # Grade J-55

New-used csg. @ 956 with 125 sacks neat cement around shoe

+ 125 sax Pace Setter 114e additives _____

Plug down @ 2:00 (AM) (PM) Date 7-29-83

Cement circulated yes No. of Sacks 20

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____