

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Drawer DD  
Artesia, NM 88210

5. LEASE LC 055696	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Boulter Federal	
9. WELL NO. 5	
10. FIELD OR WILDCAT NAME Loco Hills-Queen-Grayburg-SH	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit P, Sec. 22-T18S-R29E	
12. COUNTY OR PARISH Eddy	13. STATE NM
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3479.5' GR	

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐


2. NAME OF OPERATOR  
Martin Yates, III

3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 660 FSL & 660 FEL, Sec. 22-18S-29E  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Reperforate & Treat <input type="checkbox"/>	



RECEIVED  
SEP 29 1 34 PM '83  
BUREAU OF REVENUE  
ROSWELL, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-19-83. TD 3530'. Well pumped off (Loco Hills and Metex) perforations 2541-59' and 2673-79'. Pulled rods, pump and tubing. Pulled rods, pump and tubing. Checked for fill - none. Ran RBP and set at 2173', tested to 1300#, okay. Spotted acid at 2100'. POOH. WIH and perforated 2086-2105' w/16 .50" holes as follows: 2086-88' (2 PSF); 2097-2101' (2 SPF); 2103-05' (2 SPF). Acidized perforations w/2000 gallons 20% NEFE acid, 60 bbls 1% KCL overflush. Ran tubing, rods and pump. Began pumping back load.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Production Supervisor DATE 9-27-83

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

OCT - 3 1983

\*See Instructions on Reverse Side