

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-047633-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

The Eastland Oil Company

3. ADDRESS OF OPERATOR

P. O. Drawer 3488, Midland, TX 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980' PML & 1980' PEL of Section SW/4 NE/4 Unit "G"

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3560' GL, 3571' KB

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Sibyl Federal

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Power Grayburg San Andres

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 1, T18S, R30E

12. COUNTY OR PARISH

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

XX *

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Casing Setting

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

* Change Plans: Projected total depth changed from 3600 feet to 3700 feet in San Andres formation, Power Grayburg San Andres Pool.

Rigged up WEK Drilling Co., Inc., contractor, and spudded 12 1/4 inch hole at 10:30 a.m., August 7, 1983. Drilled to 697 feet in anhydrite @ 11:30 p.m. Ran 17 joints 230, 8 5/8 inch, #1 casing, 677.83 feet, set at 691.83 feet. Cemented with 350 sacks Class "C" 2 1/2 CaCl₂. Cement in place at 3:30 a.m. August 8, 1983. Circulated out 50 sacks excess cement. WOC 18 hours. Nipped up BOP and tested casing with 600 psi for 30 minutes-O.K. Drilled out at 3:45 a.m., August 9, 1983.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Vice President-Production

DATE August 12, 1983

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE
ACCEPTED FOR RECORD

AUG 25 1983

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1983-O-685229

847-485

