

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.O.B.	
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2080  
SANTA FE, NEW MEXICO

SEP 28 1983

O. C. D.  
ARTESIA, OFFICE

Form C-103  
Revised 10-1-78

5. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator  
Yates Petroleum Corporation

Address of Operator  
207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM  
THE East LINE, SECTION 12 TOWNSHIP 18S RANGE 25E NMPM.

7. Unit Agreement Name
8. Farm or Lease Name Merchant XT Com
9. Well No. 1
10. Field and Pool, or Wildcat Und. E. Eagle Creek Morrow
12. County Eddy

15. Elevation (Show whether DF, RT, GR, etc.)  
3437' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole 9:30 PM 9-24-83. Ran 9 joints 13-3/8" 48# J-55 casing set 358'.  
1-Texas Pattern notched guide shoe set 358'. Insert float set 317'. Cemented w/360 sacks  
Class "C" 2% CaCl<sub>2</sub>. Compressive strength of cement - 1250 psi in 12 hours. PD 4:00 PM  
9-25-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated  
25 sacks. WOC. Drilled out 4:00 AM 9-26-83. WOC 12 hours. Cut off and welded on flow  
nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements TITLE Production Supervisor DATE 9-27-83

Original Signed By  
Leslie A. Clements  
Supervisor District II

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE SEP 29 1983

CONDITIONS OF APPROVAL, IF ANY: