

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.O.S.	☒
LAND OFFICE	☒
OPERATOR	☒

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501
OCT 25 1983
O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-75

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG WELLS TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐ Name of Operator Yates Petroleum Corporation ✓ Address of Operator 207 South 4th St., Artesia, NM 88210 Location of well UNIT LETTER A 660 FEET FROM THE North LINE AND 660 FEET FROM East THE LINE, SECTION 12 TOWNSHIP 18S RANGE 25E NMPM. 15. Elevation (Show whether DF, RF, GR, etc.) 3437' GR	5a. Indicate Type of Lease State ☐ Free ☒ 5. State Oil & Gas Lease No. 7. Unit Agreement Date 8. Form or Lease Name Merchant XT Com 9. Well No. 1 10. Right and Post, or interest East Eagle Creek Morrow 12. County Eddy
--	---

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐	REMEDIAL WORK ☐ COMMENCE DRILLING OPNS. ☐ CASING TEST AND CEMENT JOBS ☐ OTHER ☒ Production Casing	ALTERING CASING ☐ PLUG AND ABANDONMENT ☐ OTHER ☒
---	--	---	--

Describe Reported or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work, SEE RULE 1103).

TD 8785'. Ran 209 joints of 4-1/2" 10.5# & 11.6# K-55 casing as follows: 50 joints 4-1/2" 11.6# K-55; 126 joints 4-1/2" 10.5# K-55 and 33 joints 4-1/2" 11.6# K-55 (total 8818') set 8785'. DV tool set 5645'. Regular guide shoe set 8785'. Insert float set 8740'. Cemented in 2 stages as follows: Stage 1: Cemented w/1050 sacks Class "H", .6% Halad-9, .5% CFR-2 and 2# KCL. Compressive strength of cement 950 psi in 12 hours. PD 9:30 AM 10-19-83. Cement circulated 75 sacks. Stage 2: Cemented w/1000 sacks Howco Lite. Tailed in w/100 sacks Class "C" Neat. Compressive strength of cement - 950 psi in 12 hours. PD 3:30 PM 10-19-83. Cement circulated 25 sacks. WOC.

I, hereby certify that the information above is true and complete to the best of my knowledge and belief.

APPROVED BY [Signature] TITLE Production Supervisor DATE 10-25-83
 APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE NOV 10 1983
 CONDITIONS OF APPROVAL, IF ANY: