

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

+  
clsr  
dp

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

RECEIVED

OCT - 9 1992

WELL API NO. 30-015-24575
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Merchant XT Com
8. Well No. 1
9. Pool name or Wildcat Undesignated Strawn
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3437' GR

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER RECOMPLETION
2. Name of Operator YATES PETROLEUM CORPORATION
3. Address of Operator 105 South 4th St., Artesia, NM 88210
4. Well Location Unit Letter A : 660 Feet From The North Line and 660 Feet From The East Line Section 12 Township 18S Range 25E NMPM Eddy County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: Plugback, perforate, treat <input checked="" type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8-25-92. Abandon Morrow by setting CIBP 8327' and capped with 35' cement. Perforated as follows: 8173-78' (12 holes), 8155-58' (8 holes), 8087-93' (14 holes), 8073-77' (10 holes), 8041-46' (12 holes). Acidized perfs 8155-8178' w/1500g. 15% NEFE acid. Acidized perfs 8041-8093' w/3000g. 15% NEFE acid. Straddled all perfs 8041-8178' and swabbed. Released tools. Set RBP @ 7950', tested to 2000#. TOH w/packer. Perforated 7832-44' (26 holes) and 7788-92' (10 holes). TIH w/packer, set @ 7711'. Tested annulus to 1000#. Swabbed dry. Acidized 7783-7844' w/3000g. 15% NEFE acid. Swabbed dry.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 10-7-92

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use) ORIGINAL SIGNED BY MIKE WILLIAMS SUPERVISOR DISTRICT I

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE OCT 1 1992

CONDITIONS OF APPROVAL, IF ANY: