

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☒

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660 FNL & 1980 FEL, Sec.36-18S-26E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

☒

FRACTURE TREAT ☐

☐

SHOOT OR ACIDIZE ☐

☐

REPAIR WELL ☐

☐

PULL OR ALTER CASING ☐

☐

MULTIPLE COMPLETE ☐

☐

CHANGE ZONES ☐

☐

ABANDON\* ☐

☐

(other) ☐

☐

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 17-1/2" hole 9:45 PM 9-30-83. Ran 13 jts of 13-3/8" 54.5# J-55 casing set 551'. Insert float set 501'. Cemented w/600 sacks Class C 3% CaCl<sub>2</sub>. Compressive strength of cement-1275 psi in 12 hrs. PD 2:00 AM 10-2-83. Bumped plug to 500 psi, released pressure and float held okay. Cement circulated 50 sacks. WOC. Drilled out 2:00 PM 10-2-83. WOC 12 hrs. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling. Ran 33 jts of 9-5/8" 36# J-55 ST&C casing set 1325'. 1-Texas Pattern notched guide shoe set 1325'. Insert float set 1290'. Cemented w/237 sacks Class C 4% gel, .3% CF-2 and 1% CaCl<sub>2</sub>. Tailed in w/301 sacks Class C 2% CaCl<sub>2</sub>. Compressive strength of cement - 1250 psi in 12 hrs. PD 1:15 AM 10-4-83. Bumped plug to 950 psi, released pressure and float held okay. Cement circulated 24 sacks. WOC. Drilled out 7:15 PM 10-4-83. WOC 18 hrs. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 8-3/4". Drilled plug and resumed drilling.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED [Signature] TITLE Production Supervisor

DATE 10-10-83

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

\*See Instructions on Reverse Side

OCT 17 1983

ROSWELL, NEW MEXICO

5. LEASE NM 34452	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Northwestern Shores XR Federal	
9. WELL NO. 1	
10. FIELD OR WILDCAT NAME Undesignated Morrow	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit B, Sec. 36-T18S-R26E	
12. COUNTY OR PARISH Eddy	13. STATE NM
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3277' GR	

RECEIVED  
OCT 12 8 47 AM '83  
BUREAU OF LAND MANAGEMENT  
ROSWELL DISTRICT

(NOTE: Report results of multiple completion on one change on Form 9-330.)