

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
PERMIT NO. 88210

SUBMIT IN TRIPLY
(Other instructions
verse side)

TE
re

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

clsf

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use APPLICATION FOR PERMIT for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR
105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
660' FNL & 1980' FEL, Sec. 36-18S-26E

RECEIVED

MAR 03 '89

O. C. D.
ARTESIA, OFFICE

14. PERMIT NO.
API #30-015-24600

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3277' GR

5. LEASE DESIGNATION AND SERIAL NO.
NM 34452

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Northwestern Shores XR Fed.

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
Four Mile Draw-Morrow Gas

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit B, Sec. 36-T18S-R26E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) Propose workover - existing zone. ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATION. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

This well is completed in Morrow perfs 9405-11', 9419-23' and 9430-38'. The lowest interval is now 100% watered out.
Propose to set a retainer at 9423', pump Temblok into perfs 9405-23', squeeze perfs 9430-38' w/75 sx Class H cement, reverse hole to clean perfs 9405-23'. WOC. Acidize perfs 9405-23'.

Will consider perforating Upper Morrow 9314-50 and stimulate for production.

RECEIVED
FEB 23 11 32 AM '89
CARLISLE
AREA OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Production Supervisor DATE 2-22-89

(This space for Federal or State office use)

APPROVED BY ORIG. SGD. RAJ GUN TITLE CHIEF, MINERAL RESOURCES DATE 3-2-89

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side