

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NEW OIL CASES. COMMISSION
SUBMIT IN THE
(Other instruct. on re-verse side)
00210

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

C/SF

5. LEASE DESIGNATION AND SERIAL NO.

NM 34452

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐
2. NAME OF OPERATOR
Yates Petroleum Corporation
3. ADDRESS OF OPERATOR
105 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
660' FNL & 1980' FEL, Sec. 36-18S-26E

RECEIVED

JUN 28 '89

O. C. D.
ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Northwestern Shores XR Fed.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Four Mile Draw-Morrow Gas

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Unit B, Sec. 36-T18S-R26E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. PERMIT NO.
API #30-015-24600

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3277' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Perforate additional Morrow

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Perforate Upper Morrow at 9314-16', 9324-27', 9330-43' with 1 SPF (21 holes - .41" holes). Acidize perms 9314-16', 9324-27', 9330-43' w/2000 gals 7½ MS acid, N₂ and 19 ball sealers.

Frac perforations 9314-9343' (21 holes) with 11000 gals Acid Gel II and CO₂ with 12000# 20/40 sand.

Recover load and return well to production.

Work began 5-24-89, completed 6-7-89.

Note: Perforations open: 9314-9343' and 9405-9411'.

18. I hereby certify that the foregoing is true and correct

SIGNATURE

TITLE Production Supervisor

DATE 6-15-89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUN 26 1989

*See Instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO