

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Pet. Corp.</u>		Lease <u>Brownwick YD ST.</u>		Well # <u>1</u>	
Location of Well	Unit <u>0</u>	Section <u>7</u>	Township <u>18 S</u>	Range <u>25 E</u>	County <u>EDDY</u>
Drilling Contractor	<u>NA</u>		Type of Equipment <u>ASAP</u>		
<p>* Witness <u>APPROVED CASING PROGRAM</u></p>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 1/2"</u>	<u>10 3/4"</u>	<u>32 #</u>	<u>NEW</u>	<u>320'</u>	<u>CITC.</u>
* <u>9 1/2"</u>	<u>7"</u>	<u>20 #</u>	<u>"</u>	<u>1052'</u>	<u>CITC.</u>
<u>6 1/2"</u>	<u>4 1/2"</u>	<u>9.5 #</u>	<u>"</u>	<u>70</u>	<u>CITC.</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected)					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>9 7/8</u> Size of Casing <u>7</u> Sacks cement required _____					
Type of Shoe used <u>Tex-Pat</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>1041</u> Set <u>1043</u> Feet of <u>7</u> Inch <u>23</u> # Grade <u>J-55</u>					
New-used csg. @ <u>1043</u> with <u>250</u> sacks neat cement around shoe					
+ <u>300</u> sac <u>Hawco lite</u> additives <u>1/4 Flo Seal</u> #5 Gilsomite #306 CC					
Plug down @ <u>3:30</u> (AM) (PM) Date <u>10-25-83</u>					
Cement circulated <u>yes</u> No. of Sacks <u>200</u>					
Cemented by <u>Hawco</u> Witnessed by <u>BLW Weaver</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>Last Drilling Break 880 Ft No Loss zone</u>					