OIL CONSER PATABOLISTS IN PROPERTY OF A COLOR	STATE OF NEW MEXICO, ENERGY AND MINERALS DEPARTMENT		
Special content proposes of Cornected Operation Toward Plant Parameter Param	DISTRIBUTION SANTA FE FILE U.S.G.S. LAND OFFICE	P. O. BOX RECEIVED BY SANTA FE, NEW MEXICO 87501 OCT 14 1983 O. C. D.	Revised 10-1-; Sa. Indicate Type of Lease State Type [X]
Platt PA Services Of Computer 207 South 4th St., Artesia, NN 88210 West 18 430 Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: Substitution 18 18 18 26 26 26 28 28 28 28 28 28 28 28 28 28 28 28 28	OIL X GAN WELL OTHER-	S AND REPORTS ON WELLS L ON TO DIEPIH OR PLUG BALK TO A DIFFERENT HESERVOIR.	7, Unit Agreement Name
West 134, NC130 26 1000 188 188 26E 112, County 3310' GR 2310' GR 2400 2400 2500 2500 2500 2500 2500 2500	Address of Operator 207 South 4th St., Artesia, NM Location of Well	The state of the s	Platt PA 9. Well No. 8 10. Fleid and Pool, or Wildeat Und. Atoka Yeso
Spudded 12-1/4" hole 3:30 PM 10-11-83. Ran 23 joints 8-5/8" 24# J-55 casing set 978'. 1- Texas Pattern notched guide shoe set 978'. Insert float set 935'. Cemented w/400 sacks Class "C" 4% Gel, 2% CaCl2. Tailed in w/200 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PJ 4:15 PM 10-12-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hours. Ran Temperature Survey and found top of cement - 130'. Ran 1". Tagged cement 85'. Spotted 200 sacks Class "C" 4% CaCl2. PD 12:00 AM 10-13-83. Cement circulated 10 sacks. WOC. Drilled out 10:15 AM 10-13-83. WOC 18 hours. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 6-1/4". Drilled plug and resumed drilling.	West LINE, SECTION 26	TOWNSHIP 18S RANGE 26E Floration (Show whether DF, RT, GR, etc.) 3310 GR	HMPM. 12. County Eddy
Spudded 12-1/4" hole 3:30 PM 10-11-83. Ran 23 joints 8-5/8" 24# J-55 casing set 978'. 1- Texas Pattern notched guide shoe set 978'. Insert float set 935'. Cemented w/400 sacks Class "C" 4% Gel, 2% CaCl2. Tailed in w/200 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 4:15 PM 10-12-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement did not circulate. WOC 6 hours. Ran Temper- ature Survey and found top of cement - 130'. Ran 1". Tagged cement 85'. Spotted 200 sacks Class "C" 4% CaCl2. PD 12:00 AM 10-13-83. Cement circulated 10 sacks. WOC. Drilled out 10:15 AM 10-13-83. WOC 18 hours. Nippled up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 6-1/4". Drilled plug and resumed drilling.	NOTICE OF INTENTION	TO: PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING OPNS. CHANGE PLANS CASING TEST AND CEMENT JQB	QUENT REPORT OF: ALTERING CASING PLUG AND ABANDONMENT
Original Signed By	Spudded 12-1/4" hole 3:30 PM 16 Texas Pattern notched guide she Class "C" 4% Gel, 2% CaCl2. Tastrength of cement - 1250 psi released pressure and float helature Survey and found top of a sacks Class "C" 4% CaCl2. PD 15 Drilled out 10:15 AM 10-13-83.	0-11-83. Ran 23 joints 8-5/8" 24# oe set 978'. Insert float set 935' ailed in w/200 sacks Class "C" 2% 0 in 12 hours. PD 4:15 PM 10-12-83. ld okay. Cement did not circulate. cement - 130'. Ran 1". Tagged cem 12:00 AM 10-13-83. Cement circulat WOC 18 hours. Nippled up and tes	J-55 casing set 978'. 1- . Cemented w/400 sacks CaC12. Compressive Bumped plug to 1000 psi, WOC 6 hours. Ran Temper- ment 85'. Spotted 200 ded 10 sacks. WOC.
Original Signed By	. I hereby certify that the information above is true a	and complete to the beat of my knowledge and belief.	
	mofulista Diroll		0CT 1 8 1483

Supervisor District II

CONDITIONS OF APPROVAL, IF ANY: