## NEW MEXICO OIL CONSERVATION COMMUSSION DRAWER DD ARTESIA, NEW MEXICO

			DRAWER IA, NEW		Ċ				
FIELD REPORT FOR CEMENTING OF WELLS									
Operator R	Lease	Lease FEDELL				Well #			
Location of Well				Townsh	ip	Range 26E	County EDDY		
Drilling Contractor		Type of Equipment RotARY							
Contractor N/A ROTARY   * Witness APPROVED CASING PROGRAM									
Size of Ho	le Size			nt Per New or		v or Used	Depth	Sacks Cement	
* 12'/4"	· 12'/4" 8		2	4 <sup>#</sup>	NEW		1000'	CIRC.	
ץ <sup>ז</sup> ק"	ę	5'/z"	10	5,5#		11	3800'	CIRC.	
			1						
Casing Data	a:				<b></b>	····,			
Surfacejoints ofinch# Grade									
(Approved) (Rejected)									
Inspected bydate									
Cementing I	Program	-							
Size of hole <u>12/4</u> Size of Casing <u>85%</u> Sacks cement required									
Type of Shoe used <u>Guide</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>yes</u>									
		et 435 Eee							
New- <del>use</del> d c:	sg. @ 93.	s with 20	00 S	acks ne	eat d	coment ar	ound sho	e	
+ 300 5	sax Heur	co Lite	additiv	ves <u>VyF</u>	=1 v Lee	1 to Gilso	vite 2%	<u>.</u>	
+ <u>300</u> sax <u>Heuro Lite</u> additives <u>y Fluded</u> 5 Gilsouite 2% cc Plug down @ <u>230</u> (AM) (PM) Date <u>11-1-83</u>									
Cement circulated No. of Sacks									
Cemented by Heuro Witnessed by BWWeaver									
Temp. Survey ran @ 1:30 (AM) (#1) Date <u>11-1-13</u> top cement @ <u>110</u>									
Casing test	t @	(AM) (F	M) Dat	t <u>e</u>			····-		
Method Used	1			Witne	5560	i by			
Checked for	shut of	f @ (AM	) (PM)	Date					
Wethod usedWitnessed by									
Remarks:	Raw 1"	to 110 Ft .	and a	neulated	W	ith sosx	Class C		
· · · · · · · · · · · · · · · · · · ·						<u></u>			
,			<u></u>						