

STATE OF NEW MEXICO.
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501
NOV 04 1983
O. C. D.
ARTESIA OFFICE

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - II" (FORM C-102) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Yates Petroleum Corporation ✓

Address of Operator
207 South 4th St., Artesia, NM 88210

Location of Well
UNIT LETTER G 23100 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 8 TOWNSHIP 18S RANGE 26E N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
Chumbley XS Com

9. Well No.
10. Field and Pool, or Wildcat
Und. Morrow

11. Elevation (Show whether DF, RT, GR, etc.)
3396' GR

12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 17-1/2" hole 7:00 AM 10-30-83. Set 45' of 20" conductor pipe. Ran 12 joints of 13-3/8" 68# K-55 casing set 440'. 1-Texas Pattern notched guide shoe set 440'. Insert float set 403'. Cemented w/400 sacks Class "C" 4% gel, 1#/sack Hiseal, 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 10:45 PM 10-30-83. Bumped plug to 1000 psi, held for 30 minutes, released pressure and float held okay. Cement circulated 25 sacks. WOC. Drilled out 10:45 AM 10-31-83. WOC 12 hours. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

14. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements TITLE Production Supervisor DATE 11-2-83
Original Signed By
Leslie A. Clements
APPROVED BY _____ TITLE Supervisor District II DATE NOV 07 1983

CONDITIONS OF APPROVAL, IF ANY: