

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	✓	
FILE	✓	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	✓	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

RECEIVED BY
NOV 15 1983
O. C. D.
ARTESIA, OFFICE

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator Yates Petroleum Corporation ✓	8. Farm or Lease Name Krauss GF
Address of Operator 207 South 4th St., Artesia, NM 88210	9. Well No. 2
Location of Well UNIT LETTER K 1750 1650 FEET FROM THE South LINE AND 1750 1650 FEET FROM West 22 TOWNSHIP 18S RANGE 26E	10. Field and Pool, or WHdcat Atoka-SA
15. Elevation (Show whether DF, RT, GR, etc.) 3330 3329 GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒
OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole 8:45 AM 11-7-83. Set 40' of 20" conductor pipe. Ran 23 joints of 8-5/8" 24# K-55 ST&C casing set at 950'. 1-Texas Pattern notched guide shoe set at 950'. Baffle float set at 907'. Cemented w/350 sacks Class "C", 4% gel, 2#/sack Hiseal and 1% CaCl2. Tailed in w/200 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 8:10 PM 11-8-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 20 sacks. WOC. Drilled out 2:10 PM 11-9-83. WOC 18 hours. NU and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements TITLE Production Supervisor DATE 11-10-83
Original Signed By
Leslie A. Clements
Supervisor District II
APPROVED BY _____ TITLE _____ DATE NOV 15 1983

CONDITIONS OF APPROVAL, IF ANY: