	MEXICO S DEPARTMENT			O VON	o 1983	
NO. OF COPIES RECEIVE		OIL CONSERVA P. O. BOX	TION DIVISION			Form C-103 - Revised 10-1-78
DISTRIBUTION SANTA FE		SANTA FE, NEW	1		C. D.	
V.S.O.S.		į	L	ARTES	State X	F•• 🗌
DPERATOR					B-8814-1	
(DO NOT USE THIS	SUNDRY NOTICE	S AND REPORTS ON	WELLS ACK TO A DIFFERENT RESERVOING PROPOSALS.)			
•	AB X OTHER-			1	7. Unit Agreement	
. Name of Operator					8. Fam or Lease Name Two Forks State	
Costa Resources, Inc.					9. Well No.	
3303 Lee Parkway, Dallas, Texas 75219					10. Field and Pool, or Wildcat	
I. Location of Well WHIT LETTER	. 660	ET FROM THE North	LINE AND	FEET FROM	Und.S.Emp	ire Morrow
	•		RANGE <u>28e</u>	}		
THE East		5. Elevation (Show whether			12. County	HHHH
		GL-3646!	<i>D1</i> , 101 , 030 , 6101 ,		Eddy	<i>711111111</i>
16.			lature of Notice, Repo	ort or Othe	er Data REPORT OF:	
МО	TICE OF INTENTION	то:	208	C C		
PERFORM REMEDIAL WORK		PLUG AND ABANDON	REMEDIAL WORK COMMENCE DRILLING OPNS.			NG CASING
TEMPORABILY ABANDON PULL OR ALTER CASING		CHANGE PLANS	CASING TEST AND CEMENT J	ı₃ [X]		
OTHER			OTHER			
	r Completed Operations (CI	early state all pertinent det	ails, and give pertinent date	s, including	stimated date of s	tarting any proposed
work) SEE RULE 11	, o 3.					
10/28/8	3-Move in and	rig up.		40	1	
10/29/8	3-Commence dri	lling, drill	to 340' in red	bed. 17	$\frac{1}{2}$ " hole.	
10/29/8 10/30/8	3-Commence dri 3-Shutdown for	lling, drill repairs.				19'.
10/29/8 10/30/8	3-Commence dri 3-Shutdown for 3-Drill to 536	lling, drill repairs. 6'. Run 14jts.	, 13 3/8" <i>5</i> 4. <i>5</i> 4	ST&C	K-55 to 51	19'. ılated
10/29/8 10/30/8	3-Commence dri 3-Shutdown for 3-Drill to 536 Cemented wit	lling, drill repairs. 5'. Run 14jts. th 575sx class	, 13 3/8" 54.5% C w/2% calcium	ST&C I	K-55 to 51	l9'. ılated
10/29/8 10/30/8 10/31/8	3-Commence dri 3-Shutdown for 3-Drill to 536 Cemented with	lling, drill repairs. 6'. Run 14jts. th 575sx class 5. Plug down 6	, 13 3/8" 54.5% C w/2% calcium :45PM. WOC 12hm	ST&C land	K-55 to 51 ide. Circu	ulated
10/29/8 10/30/8 10/31/8	3-Commence dri 3-Shutdown for 3-Drill to 536 Cemented with 55sx to pits 3-Nipple up and	clling, drill repairs. 5'. Run 14jts. th 575sx class 5. Plug down 6 d test bop and	, 13 3/8" 54.5% C w/2% calcium :45PM. WOC 12hr surface pipe	ST&C land	K-55 to 51 ide. Circu	ulated
10/29/8 10/30/8 10/31/8	3-Commence dri 3-Shutdown for 3-Drill to 536 Cemented with 55sx to pits 3-Nipple up and	lling, drill repairs. 6'. Run 14jts. th 575sx class 5. Plug down 6	, 13 3/8" 54.5% C w/2% calcium :45PM. WOC 12hr surface pipe	ST&C land	K-55 to 51 ide. Circu	ulated
10/29/8 10/30/8 10/31/8	3-Commence dri 3-Shutdown for 3-Drill to 536 Cemented with 55sx to pits 3-Nipple up and	clling, drill repairs. 5'. Run 14jts. th 575sx class 5. Plug down 6 d test bop and	, 13 3/8" 54.5% C w/2% calcium :45PM. WOC 12hr surface pipe	ST&C land	K-55 to 51 ide. Circu	ulated
10/29/8 10/30/8 10/31/8	3-Commence dri 3-Shutdown for 3-Drill to 536 Cemented with 55sx to pits 3-Nipple up and	clling, drill repairs. 5'. Run 14jts. th 575sx class 5. Plug down 6 d test bop and	, 13 3/8" 54.5% C w/2% calcium :45PM. WOC 12hr surface pipe	ST&C land	K-55 to 51 ide. Circu	ulated
10/29/8 10/30/8 10/31/8	3-Commence dri 3-Shutdown for 3-Drill to 536 Cemented with 55sx to pits 3-Nipple up and	clling, drill repairs. 5'. Run 14jts. th 575sx class 5. Plug down 6 d test bop and	, 13 3/8" 54.5% C w/2% calcium :45PM. WOC 12hr surface pipe	ST&C land	K-55 to 51 ide. Circu	ulated
10/29/8 10/30/8 10/31/8 11/1/83	3-Commence dri 3-Shutdown for 3-Drill to 536 Cemented with 55sx to pits 3-Nipple up and Scheduled to	lling, drill repairs. 5'. Run 14jts. th 575sx class 5. Plug down 6 d test bop and resume drilli	, 13 3/8" 54.5% C w/2% calcium :45PM. WOC 12hr surface pipe - ng 11AM.	ST&C la chlor	K-55 to 51 ide. Circu	ulated
10/29/8 10/30/8 10/31/8 11/1/83	3-Commence dri 3-Shutdown for 3-Drill to 536 Cemented with 55sx to pits 3-Nipple up and Scheduled to	ching, drill repairs. 6'. Run 14jts. th 575sx class 7. Plug down 6 1 test bop and 1 resume drilli	, 13 3/8" 54.5% C w/2% calcium:45PM. WOC 12hr surface pipe ng 11AM.	ST&C la chlor	K-55 to 51 ide. Circu	ulated
10/29/8 10/30/8 10/31/8 11/1/83	3-Commence dri 3-Shutdown for 3-Drill to 536 Cemented with 55sx to pits 3-Nipple up and Scheduled to	lling, drill repairs. 5'. Run 14jts. th 575sx class 5. Plug down 6 d test bop and resume drilli	, 13 3/8" 54.5% C w/2% calcium:45PM. WOC 12hr surface pipe ng 11AM.	ST&C n chlor	K-55 to 51 ide. Circu psi. for 3	ulated

CONDITIONS OF APPROVAL, IF ANYS