

Drawer - - - - -
Artesia, NM 88210
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYRECEIVED BY
SUBMIT IN PLICATE*NOV 28 1983
Other instructions on
reverse side56-015-24693
Form approved.
Budget Bureau No. 42-R1425.

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. NM - 23414	
b. TYPE OF WELL OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> SINGLE ZONE <input type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR Anadarko Production Company ✓		7. UNIT AGREEMENT NAME	
3. ADDRESS OF OPERATOR P. O. Drawer 130, Artesia, New Mexico 88210		8. FARM OR LEASE NAME Travis "E" Federal	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)* At surface 500' FS & WLs Sec. 6, T18S, R29E At proposed prod. zone Same Eddy County, New Mexico		9. WELL NO. 2	
14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE* Approximately 7 miles Southwest of Loco Hills, New Mexico		10. FIELD AND POOL, OR WILDCAT Loco Hills-Queen-Grayburg-San Andres	
15. DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drlg. unit line, if any) 500'		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 6 - 18S - 29E	
16. NO. OF ACRES IN LEASE Approx. 140		12. COUNTY OR PARISH Eddy	
17. NO. OF ACRES ASSIGNED TO THIS WELL 30.05		13. STATE New Mexico	
18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. 1850'		20. ROTARY OR CABLE TOOLS Rotary	
21. ELEVATIONS (Show whether DF, RT, GR, etc.) 3630.9' GL		22. APPROX. DATE WORK WILL START* Dec. 12, 1983	

23. PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
12-1/4"	8-5/8"	24.0#	325 350'	Approx. 250 sx circ or readymixed
7-7/8"	5-1/2"	15.5#	2775'	Approx. 500 circulated

1. Rig up rotary tools.
2. Drill 12-1/4" hole to approx. 350'; set & circulate or readymix cement to surface on 8-5/8" casing. Install & test Series 900 Double Ram Hydraulic Blowout Preventor.
3. Drill 7-7/8" hole to T D (approx. 2775'); run Open Hole Logs.
4. Set & circulate cement on 5 1/2" casing from T D to surface.
5. Perforate, acidize and fracture treat.
6. Run 2-3/8" tubing, rods and bottomhole pump; install pumping equipment and place well on production.

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED Truman D. Jones TITLE Field Foreman DATE November 7, 1983

(This space for Federal or State office use)

PERMIT NO.

APPROVAL DATE

APPROVED BY

/s/ Earl R. Cunningham

TITLE

District Manager
BLM

DATE

11-23-83

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions On Reverse Side

APPROVAL SUBJECT TO
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS
ATTACHED