

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION

P. O. BOX 2088

SANTA FE, NEW MEXICO

RECEIVED

APR 10 1984

O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
LG 3215

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Yates Drilling Company

3. Address of Operator
207 South 4th St., Artesia, NM 88210

4. Location of Well
UNIT LETTER L 2100 FEET FROM THE South LINE AND 330 FEET FROM THE West LINE, SECTION 20 TOWNSHIP 18S RANGE 28E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
Mesa State 20-1 State

9. Well No.
1

10. Field and Pool, or Wildcat
Unders. Artesia

11. Elevation (Show whether DF, RT, GR, etc.)
3599' GR

12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☒

CASING TEST AND CEMENT JOB ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 12-1/4" hole at 1:30 PM 4-4-84. Ran 9 joints of 8-5/8" 34 # casing set at 362'. 1-Texas Pattern notched guide shoe set at 362'. Insert float set at 321'. Cemented w/100 sacks Class "C" 25% Lite Poz, 1/4#/sack flocele, 5#/sack Kolite and 3% CaCl2. Tailed in w/135 sacks Class "C" 3% CaCl2. Compressive strength of cement-1275 psi in 12 hours. PD 8:30 PM 4-4-84. Bumped plug to 750 psi, released pressure and float held okay. Cement circulated 25 sacks. WOC. Drilled out at 9:00 AM 4-5-84. WOC 12 hours and 30 minutes. Nipped up and tested to 1000 psi for 30 minutes, okay. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Production Supervisor DATE 4-10-84

APPROVED BY [Signature] TITLE Geologist DATE 4-11-84

CONDITIONS OF APPROVAL, IF ANY: