

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87504

O. C. D.  
ARTESIA, OFFICE

Form C-103  
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒

GAS WELL ☐

OTHER ☐

Name of Operator

Yates Drilling Company ☒

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER L, 2100 FEET FROM THE South LINE AND 330 FEET FROM THE West LINE, SECTION 20 TOWNSHIP 18S RANGE 28E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3599' GR

5a. Indicate Type of Lease

State ☒

Fee ☐

5. State Oil & Gas Lease No.

LG 3215

7. Unit Agreement Name

8. Farm or Lease Name

Mesa 20-1 State

9. Well No.

1

10. Field and Pool, or Wildcat

Unders. Artesia SA

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☐

OTHER Production Csg, Perforate, Treat ☒

OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 2510'. Ran 63 joints of 5-1/2" 14# J-55 ST&C casing set at 2508'. Float shoe set at 2509'. Cemented w/150 sacks C 50/50 Lite Poz III, 1/4#/sack flocele and 1% CaCl2. Tailed in w/100 sacks Self Stress cement. Compressive strength of cement - 500 psi in 12 hours. PD 5:45 PM 4-9-84. Bumped plug to 1000 psi, released pressure and float held okay. WOC 18 hours. WIH and perforated 2407-14' w/10 .48" holes. Acidized perfs 2407-14' w/750 gallons 15% acid. Swab testing well.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements

TITLE Production Supervisor

DATE 4-20-84

Original Signed By

Leslie A. Clements

Supervisor District II

APPROVED BY

TITLE

DATE

APR 24 1984

CONDITIONS OF APPROVAL, IF ANY: