					_		<i>(</i>
orm 3160-5	UNI1ED S	TATES	SUBMIT IN TRIP	LICATE*	Form ap Budget	Bureau 1	Vo. 1004-0135
ormerly 9-331) DEPA		THE INTERIO	R (Other instruction verse side)	os on re-	LEASE DESI	ONATION	31, 1985
BU	REAU OF LAND	MANAGEMENT				1 2927:	
(Do not use this form for t	roposals to drill or t	REPORTS ON o deepen or plug back MIT—" for such propo	to a different reserve	GCENVEV.	. IF INDIAN,	ALLOTTEE	OR TRIBE NAME
		e e m	OF LAND MAN		UNIT AGREE	MENT NA	×E
WELL WELL & OTH NAME OF OPERATOR	ER				. FARM OR LI		
Amoco Production C	ompany		NEGENTED A	See Nacial -	Federal		
ADDRESS OF OPERATOR				RTESIA OFFE	EWBLL NO.	Dir Ua.	
LOCATION OF WELL (Report local			FEB26 1990 te requirements.*		0. FIELD AND	1	WILDCAT
See also space 17 below.) At surface			ST. 6 N.M.			-	w Morrow
700' FSL x 990' FW	L (Unit M. SW	/4 SW/4)	N.M. O N.M.	<u>,</u> ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	1. SHC., T., R.		
			bad. New 18			18/27	
. PERMIT NO.	15. BLEVATIONS	S (Show whether DF, RT,	( OR, etc. )		2. COUNTY OF	R PARISH	18. STATE
		3546.C' GR			Eddy		NM
. Check	Appropriate Box	x To Indicate Nati	ure of Notice, Rep	ort, or Oth	er Data		
NOTICE OF	NTENTION TO :			SUBSEQUEN:	T REPORT OF	:	
TEST WATER SHUT-OFF	PULL OR ALTER C	ASING	WATER SHUT-OFF		REF	PAIRING W	BLL
FRACTURE TREAT	MULTIPLE COMPL	ETE	FRACTURE TREATM			BRING CA	t
RUGOT OF ACIDITE	LD ANDON .				A B A	NDONMEN	
SHOOT OR ACIDIZE	ABANDON® Change plans		SHOOTING OR ACID	<u></u>			v
REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11	CHANGE PLANS DOPERATIONS (Clearly rectionally drilled, give 89. Load tu	bing with 368	(Other) (NOTE: Repo Completion of etails, and give pertin and measured and to BW rotary to	Recompetition or results of r Recompletion rue vertical d	npletion multiple con on Report and luding estim lepths for all install	blowou	x m.) of starting any and sones perti-
REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11 and released packe release Vann guns a 1-9/16" guns: 978	CHANGE PLANS D OPERATIONS (Clearly rectionally drilled, giv (89. Load tu c. Set packe and run wirel 9-9895, 9835- lown tubing w	bing with 368 r @ 9627'. R ine to 10,000 9846. Instal ith 2000 gal.	(Other) (Norr: Repo Completion of tails, and give pertin and measured and to BW rotary to Cun shifting t ' and pull ou 1 tree saver 7-1/2% MS ac	Recon rt results of or Recompletic rue vertical d cool and i cool on w it of hol and pump	npletion maltiple con a Report an luding estim lepths for all vireline le. Per b 88 bbl	blowor to 90 fed w:	x of starting any of starting any and some perti- ut prevente 655' and ith ud down
REPAIR WELL (Other) 7. DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11 and released packe release Vann guns a 1-9/16" guns: 978 casing. Acidized Flush with 41 BW. Shut well in and r	CHANGE PLANS D OPERATIONS (Clearly rectionally drilled, giv / 89. Load tu c. Set packe and run wirel 9-9895, 9835- lown tubing w ig down servi	bing with 368 r @ 9627'. R ine to 10,000 9846. Instal ith 2000 gal. ce unit 01/04	(Other) (Norr: Repo Completion of tails, and give pertin and measured and to BW rotary to Cun shifting t ' and pull ou 1 tree saver 7-1/2% MS ac	Recon rt results of or Recompletic rue vertical d cool and i cool on w it of hol and pump	npletion maltiple con a Report an luding estim lepths for all vireline le. Per b 88 bbl	blowor to 90 fed w:	x of starting any of starting any and some perti- ut prevente 655' and ith ud down
REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11, and released packe release Vann guns a 1-9/16" guns: 978 casing. Acidized of Flush with 41 BW. Shut well in and r Unsuccessful recomp	CHANGE PLANS D OPERATIONS (Clearly rectionally drilled, giv (89. Load tu c. Set packe and run wirel 9-9895, 9835- lown tubing w ig down servi oletion to th	bing with 368 r @ 9627'. R ine to 10,000 9846. Instal ith 2000 gal. ce unit 01/04	(Other) (Norr: Repo Completion of tails, and give pertin and measured and to BW rotary to Cun shifting t ' and pull ou 1 tree saver 7-1/2% MS ac	Recon rt results of or Recompletic rue vertical d cool and i cool on w it of hol and pump	npletion maltiple con a Report an luding estim lepths for all vireline le. Per b 88 bbl	blowor to 90 fed w:	x of starting any of starting any and some perti- ut prevente 655' and ith ud down
REPAIR WELL (Other) DESCRIBE PROFOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11 and released packe release Vann guns a 1-9/16" guns: 978 casing. Acidized Flush with 41 BW. Shut well in and r	CHANGE PLANS D OPERATIONS (Clearly rectionally drilled, giv (89. Load tu c. Set packe and run wirel 9-9895, 9835- lown tubing w ig down servi oletion to th	bing with 368 r @ 9627'. R ine to 10,000 9846. Instal ith 2000 gal. ce unit 01/04	(Other) (Norr: Repo Completion of tails, and give pertin and measured and to BW rotary to Cun shifting t ' and pull ou 1 tree saver 7-1/2% MS ac	Recon rt results of or Recompletic rue vertical d cool and i cool on w it of hol and pump	npletion maltiple con a Report an luding estim lepths for all vireline le. Per b 88 bbl	blowor to 90 fed w:	x of starting any of starting any and some perti- ut prevente 655' and ith ud down
REPAIR WELL (Other) 7. DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11, and released packe release Vann guns a 1-9/16" guns: 978 casing. Acidized of Flush with 41 BW. Shut well in and r Unsuccessful recomp	CHANGE PLANS D OPERATIONS (Clearly rectionally drilled, giv (89. Load tu c. Set packe and run wirel 9-9895, 9835- lown tubing w ig down servi oletion to th	bing with 368 r @ 9627'. R ine to 10,000 9846. Instal ith 2000 gal. ce unit 01/04	(Other) (Norm: Repo Completion of tails, and give pertin and measured and to B BW rotary to Cun shifting t ' and pull ou 1 tree saver 7-1/2% MS ac	Recon rt results of or Recompletic rue vertical d cool and i cool on w it of hol and pump	npletion multiple con on Report and cluding estim lepths for all vireline le. Per o 88 bbl 150 ball	blowor to 90 fed w seale	x of starting any of starting any and some perti- ut prevente 655' and ith ud down
REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11, and released packe release Vann guns a 1-9/16" guns: 978 casing. Acidized of Flush with 41 BW. Shut well in and r Unsuccessful recomp	CHANGE PLANS D OPERATIONS (Clearly rectionally drilled, giv (89. Load tu c. Set packe and run wirel 9-9895, 9835- lown tubing w ig down servi oletion to th	bing with 368 r @ 9627'. R ine to 10,000 9846. Instal ith 2000 gal. ce unit 01/04	(Other) (Norr: Repc Completion of realls, and give perting and measured and to BW rotary to cun shifting to and pull ou 1 tree saver 7-1/2% MS ac 9/90.	Recompletion or results of or Recompletion rue vertical d cool and in cool on w it of hold and pump cid and in FOR FOR	npletion multiple con on Report and cluding estim lepths for all vireline le. Per o 88 bbl 150 ball	blowor to 90 fed w seale	x of starting any of starting any and some perti- ut prevente 655' and ith ud down
REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11 and released packe release Vann guns a 1-9/16" guns: 978 casing. Acidized Flush with 41 BW. Shut well in and r Unsuccessful recomp Well is presently a	CHANGE PLANS D OPERATIONS (Clearly rectionally drilled, giv (89. Load tu c. Set packe and run wirel 9-9895, 9835- down tubing w ig down servi oletion to th shut in	bing with 368 r @ 9627'. R ine to 10,000 9846. Instal ith 2000 gal. ce unit 01/04 e Morrow.	(Other) (Norr: Repc Completion of realls, and give perting and measured and the BW rotary to Run shifting to and pull ou 1 tree saver 7-1/2% MS ac 9/90.	Recompletion or results of or Recompletion rue vertical d cool and in cool on w it of hold and pump cid and in FOR FOR	npletion multiple com a Report and suding estim install vireline le. Per b 88 bbl 50 ball	blowor to 90 fed w: seale	x of starting any of starting any and some perti- ut prevente 655' and ith ud down
REPAIR WELL (Other) DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11 and released packe release Vann guns a 1-9/16" guns: 978 casing. Acidized Flush with 41 BW. Shut well in and r Unsuccessful recomp Well is presently a	CHANGE PLANS D OPERATIONS (Clearly rectionally drilled, giv (89. Load tu c. Set packe and run wirel 9-9895, 9835- down tubing w ig down servi oletion to th shut in	bing with 368 r @ 9627'. R ine to 10,000 9846. Instal ith 2000 gal. ce unit 01/04 e Morrow.	(Other) (Norr: Repc Completion of realls, and give perting and measured and the BW rotary to Run shifting to and pull ou 1 tree saver 7-1/2% MS ac 9/90.	Recompletion recompletion recompletion rue vertical d pool and in cool on w it of hold and pump cid and 1 recompletion and pump cid and 1 AR 71 AR 71	ABCORCE	blowor to 90 fed w seale	x on Well m.) of starting any and sones perti- ut prevente 655' and ith ud down ers.
REPAIR WELL (Other) T DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11 and released packe release Vann guns a 1-9/16" guns: 978" casing. Acidized of Flush with 41 BW. Shut well in and r Unsuccessful recomp Well is presently a L i hereby certify that the foregot	CHANGE PLANS D OPERATIONS (Clearly rectionally drilled, give (89. Load tu c. Set packe and run wirel D-9895, 9835- down tubing w ig down servi oletion to th shut in. mg is true and correct w Hel	bing with 368 r @ 9627'. R ine to 10,000 9846. Instal ith 2000 gal. ce unit 01/04 e Morrow.	(Other) (Norm: Repo Completion of tails, and give pertines and measured and to B BW rotary to bun shifting to and pull ou 1 tree saver 7-1/2% MS ac 9/90.	Recompletion recompletion recompletion rue vertical d pool and in cool on w it of hold and pump cid and 1 recompletion and pump cid and 1 AR 71 AR 71	npletion multiple com a Report and suding estim install vireline le. Per b 88 bbl 50 ball	blowor to 90 fed w seale	x of starting any of starting any and some perti- ut prevente 655' and ith ud down
REPAIR WELL (Other) 7. DESCRIBE PROPOSED OR COMPLETE proposed work. If well is d nent to this work.)* Moved rig on 12/11, and released packe release Vann guns a 1-9/16" guns: 978 casing. Acidized of Flush with 41 BW. Shut well in and r Unsuccessful recomp Well is presently a Well is presently a SIGNED A COMPLETE Methodson on the foregol	CHANGE PLANS D OPERATIONS (Clearly rectionally drilled, give (89. Load tu c. Set packe and run wirel D-9895, 9835- down tubing w ig down servi oletion to th shut in. mg is true and correct w Hel	bing with 368 r @ 9627'. R ine to 10,000 9846. Instal ith 2000 gal. ce unit 01/04 e Morrow.	(Other) (Norm: Repo Completion of tails, and give pertines and measured and to B BW rotary to bun shifting to and pull ou 1 tree saver 7-1/2% MS ac 9/90.	Recompletion recompletion recompletion rue vertical d pool and in cool on w it of hold and pump cid and 1 recompletion and pump cid and 1 AR 71 AR 71	ABCORCE	blowor to 90 fed w seale	x on Well m.) of starting any and sones perti- ut prevente 655' and ith ud down ers.