

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Exp 11-22-84

Operator <u>Blanco Engineering Inc.</u>		Lease <u>Scripps</u>		Well # <u>4</u>	
Location of Well	Unit <u>M</u>	Section <u>25</u>	Township <u>18</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor	<u>La Rue</u>		Type of Equipment <u>Rotary</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <u>12 1/4</u>	<u>8 5/8</u>	<u>24#</u>		<u>930</u>	<u>Circ</u>
<u>7 7/8</u>	<u>5 1/2</u>	<u>15.5#</u>		<u>3700</u>	<u>Circ</u>

Casing Data:

Surface 24 joints of 8 5/8 inch 24 # Grade J-55

yes

(Approved) (Rejected)

Inspected by BW Weaver date 5-25-84

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required

Type of Shoe used Tex-A-Float collar used Insert Btm 3 jts welded yes

ID of hole 937 Set 944 Feet of 8 5/8 Inch 24 # Grade J-55

New-~~used~~ csg. @ 944 with 200 sacks neat cement around shoe

+ 300 sax Hawco lite additives 1/4 LB Floal #6 Gilsomite 2% CC

Plug down @ 7:00 (AM) (PM) Date 5-25-84

Cement circulated yes No. of Sacks 40

Cemented by Hawco Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last Drilling Break @ 871