

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO

Form C-103  
Revised 10-1-78

RECEIVED BY

JUN 05 1984

O. C. D.

ARTESIA OFFICE

5. Indicate Type of Lease  
State ☐ Fee ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A WELL. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Blanco Engineering, Inc. <input checked="" type="checkbox"/>	8. Farm or Lease Name Scripps
3. Address of Operator 116 North First Street, Artesia, New Mexico 88210	9. Well No. 4
4. Location of Well UNIT LETTER <u>M</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> NMPM.	10. Field and Pool or Wildcat <u>Atoka/Yeso</u>
15. Elevation (Show whether DF, RT, GR, etc.) 3283 GR	12. County Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒ OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7 7/8" hole to 3750'. Ran 5 1/2"-17#-J555-New Casing to 3749'. Circulated and cleaned hole. Cemented casing with 400 sacks of Howco Lite, 350 sacks of 50/50 Pozmix, used 1/4# Flocele per sack, 2% Gel, 4# salt/sack, 3/10% CFR-2, 4/10% Halad 4. Cement circulated to surface. Approx. 70 sacks to pit. Job completed June 1, 1984. After 12 hours tested casing to 2500 psig for 30 minutes. Held O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Sam White TITLE V. President DATE 6-4-84

APPROVED BY Danny Brooks TITLE Geologist DATE 6-5-84

CONDITIONS OF APPROVAL, IF ANY: