

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instruction on reverse side)

Form approved.
Budget Bureau No. 42-R1424

45F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a well on a reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
CASA PETROLEUM, INC. ✓

3. ADDRESS OF OPERATOR
105 North 6th, Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)
At surface
1880' FNL & 1830' FWL of Section (Unit F)
(SE $\frac{1}{4}$ NW $\frac{1}{4}$)

14. PERMIT NO. --

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3536' KB

RECEIVED BY
AUG 03 1984
O. C. D.
ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.
NM-36497

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
--

7. UNIT AGREEMENT NAME
--

8. FARM OR LEASE NAME
ANADARKO 13 FEDERAL

9. WELL NO.
1

10. FIELD AND POOL OR WILDCAT
Artesia Oil Pool

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 13-18S-27E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Plugging Back & Running Casing X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well spudded 6-18-84.

8 5/8" (24#) casing was run in 12 1/4" hole to depth of 328' and cemented with 200 sacks of Class C cement. Plug down at 4:00 pm on 6-19-84. Circulated 45 sacks to pit.

Reached TD of 3020' on 6-25-84. Plugged back to depth of 2113' with 290 sacks of Life Weight.

5 1/2" (15.5#, K-55) casing was run in 7 7/8" hole to depth of 2113' and cemented with 485 sacks of cement. Plug down at 9:15 pm on 6-26-84. Found top of cement at 520' by Temperature Survey.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE July 5, 1984

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL ANY

Carlsbad,

NEW MEXICO

*See Instructions on Reverse Side