

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

*Epp.*

Operator <b>YPC</b>		Lease <b>GATES AAC</b>		Well # <b>1</b>	
Location of Well	Unit <b>C</b>	Section <b>22</b>	Township <b>18</b>	Range <b>26</b>	County <b>EDDY</b>
Drilling Contractor	<b>Larue</b>		Type of Equipment <b>Rotary</b>		

\* = CSG. TO WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cemen
* 12 1/4	8 5/8	24#	NEW	950	CIRC
7 7/8	4 1/2 or 5 1/2	9.5 or 14.	"	TD	CIRC

Casing Data:

Surface 27 joints of 8 5/8 inch 24 # Grade J-55  
Yes (Approved) (Rejected)

Inspected by BW Weaver date 11-20-84

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 150

Type of Shoe used Tex-Pat Float collar used Insert Btm 3 jts welded Yes

TD of hole 926 Set 927 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 927 with 150 sacks neat cement around shoe

+ 325 sax Pace Setter ltr additives 32 CC

Plug down @ 3:30 (AM) (PM) Date 9-21-84

Cement circulated Yes No. of Sacks 35

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last Drilling Break @ 820