


STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501



Form C-103  
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
Name of Operator Yates Petroleum Corporation		5. State Oil & Gas Lease No.
Address of Operator 207 South 4th St., Artesia, NM 88210		7. Unit Agreement Name
Location of Well UNIT LETTER <u>K</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>26</u> TOWNSHIP <u>18S</u> RANGE <u>26E</u> NMPM.		8. Farm or Lease Name Platt PA
15. Elevation (Show whether DF, RT, GR, etc.) 3311' GR		9. Well No. 10
12. County Eddy		10. Field and Pool, or Wildcat Atoka Glorieta Yeso

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

3. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole 8:25 AM 8-19-84. Ran 24 jts of 8-5/8" 24# J-55 casing set 945'. Texas Pattern notched guide shoe set 945'. Insert float set 904'. Cemented w/450 sx Pacemaker Lite w/10#/sx Hiseal, 1/4#/sx celloseal, 3% CaCl2. Tailed in w/150 sx Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 11:00 AM 8-20-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 40 sx to pit. WOC. Drilled out 5:00 AM 8-21-84. WOC 18 hrs. Cut off and welded on flow nipple. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Larry Brooks TITLE Production Supervisor DATE 8-22-84

PROVED BY ORIGINAL SIGNED BY LARRY BROOKS TITLE GEOLOGIST - NMOC DATE AUG 27 1984

CONDITIONS OF APPROVAL, IF ANY