

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DD  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Exp. 1-26-85

Operator YPC		Lease PLATT PA		Well # 10	
Location of Well	Unit K	Section 26	Township 18	Range 26	County EDDY
Drilling Contractor	LARUE		Type of Equipment ROTARY		

\* = CSG. TO WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cemen
* 12 1/4	8 5/8	24 #	NEW	950	CIRC
7 7/8	4 1/2 or 5 1/2	9.5 # or 14 #	"	TD	500 SX OR CIRC

Casing Data:

Surface 24 joints of 8 5/8 inch 24 # Grade J-53

Yes (Approved) (Rejected)

Inspected by BW Weaver date \_\_\_\_\_

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 150

Type of Shoe used Tex-A-Float collar used Insert Btm 3 jts welded yes

TD of hole 945 Set 949 Feet of 8 5/8 inch 24 # Grade J-55

New-used csg. @ 949 with 150 sacks neat cement around shoe

+ 450 sax Pine Solter lite additives 3% CC

Plug down @ 11:00 (AM) (PM) Date 8-20-84

Cement circulated yes No. of Sacks 40

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: Last Drilling Break 840