

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION  
P. O. BOX 2000  
SANTA FE, NEW MEXICO 87501  
**RECEIVED BY**  
**SEP 06 1984**  
**O. C. D.**  
**ARTESIA, OFFICE**

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease  
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER L 2310 FEET FROM THE South LINE AND 330 FEET FROM  
THE West LINE, SECTION 26 TOWNSHIP 18S RANGE 26E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Platt PA

9. Well No.

11

10. Field and Pool, or WHdeat  
Atoka Glorieta Yeso

15. Elevation (Show whether DF, RT, GR, etc.)

3318' GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☒  
CASING TEST AND CEMENT JOBS ☒

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 12-1/4" hole 6:45 PM 8-30-84. Ran 23 jts of 8-5/8" 24# J-55 casing set 930'. 1-Texas Pattern notched guide shoe set 930'. Insert float set 889'. Cemented w/210 sx Lite weight w/3% CaCl2, 1/4#/sack celloseal and 5#/sack Hiseal. Tailed in w/150 sx Class "C" w/2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 8:15 PM 8-31-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 53 sacks. WOC. Drilled out 2:15 PM 9-1-84. WOC 18 hrs. Cut off and welded on flow nipple. Reduced hole to 7-7/8". Drilled plug and resumed drilling. *Permanently sealed off for 30 days.*

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Larry Brooks TITLE Production Supervisor

DATE 9-6-84

APPROVED BY ORIGINAL SIGNED BY LARRY BROOKS  
CONDITIONS OF APPROVAL, IF ANY: GEOLOGIST - NMOCD

TITLE \_\_\_\_\_

DATE SEP 11 1984