

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

AUG 14 1984

O. C. D.  
ARTESIA, OFFICE

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL  
WELL ☒

GAS  
WELL ☐

OTHER-

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 So. 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER P 330 FEET FROM THE South LINE AND 990 FEET FROM  
THE East LINE, SECTION 27 TOWNSHIP 18S RANGE 26E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Kleeman PB

9. Well No.

3

10. Field and Pool, or Wildcat  
Atoka Glorieta Yeso

15. Elevation (Show whether DF, RT, GR, etc.)

3339' GR

12. County

Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

ULL OR ALTER CASING ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING (PHS) ☒

CASING TEST AND CEMENT JOB ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

1. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

Spudded 12-1/4" hole 6:16 PM 8-7-84. Ran 23 jts of 8-5/8" 24# J-55 ST&C casing set 920'. 1-Texas Pattern notched guide shoe set 920'. Insert float set 879'. Cemented w/450 sx Pacesetter Lite w/Class C base, 10# Hiseal, 1/4# cellosal and 3% CaCl2. Tailed in w/150 sx Class C 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 9:11 PM 8-8-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 35 sx. WOC. Drilled out 3:15 PM 8-9-84. WOC 18 hrs. Cut off and welded on flow nipple. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

*Leslie A. Clements*

TITLE Production Supervisor

DATE 8-10-84

PROVED BY

Original Signed By

Leslie A. Clements TITLE

DATE

AUG 22 1984

CONDITIONS OF APPROVAL, IF ANY:

Supervisor District II